

CC-Link IE TSN
Product Catalog

e-Factory



CC-Link **IE** TSN

GLOBAL IMPACT OF MITSUBISHI ELECTRIC



Through Mitsubishi Electric's vision, "Changes for the Better" are possible for a brighter future.

Changes for the Better

"Changes for the Better" represents the Mitsubishi Electric Group's attitude to "always strive to achieve something better", as we continue to change and grow. Each one of us shares a strong will and passion to continuously aim for change, reinforcing our commitment to creating "an even better tomorrow".

Mitsubishi Electric is involved in many areas including the following:

Energy and Electric Systems

A wide range of power and electrical products from generators to large-scale displays.

Electronic Devices

A wide portfolio of cutting-edge semiconductor devices for systems and products.

Home Appliance

Dependable consumer products like air conditioners and home entertainment systems.

Information and Communication Systems

Commercial and consumer-centric equipment, products and systems.

Industrial Automation Systems

Maximizing productivity and efficiency with cutting-edge automation technology.

Our advances in AI and IoT are adding new value to society in diverse areas from automation to information systems. The creation of game-changing solutions is helping to transform the world, which is why we are honored to be recognized in the 2019 "Forbes Digital 100" as one of world's most influential digital corporations.



Committed to ever-higher customer satisfaction

Mitsubishi Electric is a global leader in researching, manufacturing and marketing electrical and electronic equipment used in areas such as communications, consumer electronics, industrial technology, energy and transportation. Within this, the industrial automation business has grown significantly since the first induction motor was manufactured over 90 years ago and has closely followed the automation industry in Japan, Asia, and beyond. Mitsubishi Electric industrial automation boasts a wide range of product areas such as production control, drives, and mechatronics that are used in various industries. The company also offers e-F@ctory and iQ Platform, leveraging its total industrial automation solution portfolio.



Realizing a smart factory with an open integrated network

Creating a smart factory requires the real-time collection of shop floor data, utilizing edge-computing devices to enable point-of-origin processing, and instantaneously feeding back results to the processing machine, cloud or other IT systems. This must all be done over a robust, high-speed network having a large-capacity data bandwidth capable of transmitting large volumes of data seamlessly across the factory while maintaining deterministic control of all systems. Mitsubishi Electric products provide the interconnectivity required for entire factories to realize IIoT*1 infrastructures, simultaneously improving productivity and quality while reducing overall cost.

*1. IIoT: Industrial Internet of Things

INDEX


Features.....	8
System configuration	16
Master stations	18
Drives/GOT (HMI).....	20
Block-type remote modules	23
Managed Ethernet switch/bridge module	30
Partner products	31
Development kit/tool	32
General specifications	34
Support.....	38
Product list	42

The contents described in this catalog include features that will be supported in the future.
Specifications may change without prior notice.

e-F@ctory

Maximize productivity and reduce costs with an intelligent smart factory solution

Intelligent smart factories utilize high-speed networks with large data bandwidths to meet current manufacturing needs. The combination of CC-Link IE TSN and Mitsubishi Electric's e-F@ctory solution ensures robust integration between IT and factory automation systems, providing an intelligent smart factory solution that reduces total cost while improving operations, production yield, and efficient management of the supply chain. e-F@ctory is the Mitsubishi Electric solution for adding value across the manufacturing enterprise by enhancing productivity, thereby simultaneously reducing maintenance and operating costs, and enabling the seamless flow of information throughout the plant. e-F@ctory uses a combination of factory automation and IT technologies in combination with various best-in-class partner products through its alliance program.



e-F@ctory

CC-Link IE TSN

- IT integration
- Open technology

- High speed, Time synchronization
- Network integration

MELSEC iQ-R

GOT2000


MELSEC iQ-F

MELFA FR

MELSERVO-J5

FREQROL-A800/E800

MITSUBISHIELECTRIC
CNC C80





Open integrated networking across the manufacturing enterprise

Leveraging an integrated and open network utilizing TSN*1 technology realizes real-time data collection from the shop floor to IT systems

CC-Link IE TSN supports TCP/IP communications and applies it to industrial architectures through its support of TSN enabling real-time communications. With its flexible system architecture and extensive setup and troubleshooting features make CC-Link IE TSN ideal for building an IIoT infrastructure across the manufacturing enterprise.

*1. TSN: Time Sensitive Networking



CC-Link IE TSN is an open industrial network inheriting the easy diagnostics of the CC-Link IE Field Network, the large-capacity data communications of the CC-Link IE Control Network, and the high-performance motion control features of SSCNET. Through the incorporation of TSN technology, this network further leverages control system performance to realize an open integrated network with advanced functionality.



CC-Link IE TSN
"IIoT system" movie




CC-Link IE TSN
"Integrated motion" movie

What is Time-Sensitive Networking (TSN)?

TSN is the IEEE-defined standard technology that enables deterministic messaging on standard Ethernet. The technology ensures deterministic communications by utilizing the time synchronization method (IEEE 802.1AS) and time-sharing method (IEEE 802.1Qbv). With the addition of these standards to Ethernet technology, real-time control communication and non-real time information communication can be mixed, which is not possible with conventional Ethernet communications.

TSN Technology : Features utilizing TSN technology



Real-time and synchronized communications enabling high-accuracy motion control and event processing

Performance

Current manufacturing trends are utilizing AI and predictive maintenance to ensure high productivity and quality are achieved simultaneously. This requires high-speed communication and deterministic control of large volumes of data to IT systems. The innovative communication technology of CC-Link IE TSN increases communication performance, enables highly accurate motion control and high-speed I/O control without adversely affecting operating performance.

Intelligence

Intelligent networks that support industrial communications to realize easy device setup and preventive maintenance are essential for efficient operations. CC-Link IE TSN supports third-party diagnostic software, enabling troubleshooting of network devices (including standard Ethernet). Network event errors are time-stamped, enabling the actual cause of error to be easily evaluated. In addition, automatic generation of network system architectures and parameters simplifies commissioning.

Connectivity

CC-Link IE TSN is the key to realizing real-time communication in manufacturing systems utilizing TCP/IP-compatible Ethernet-based networks. It also enables third-party networks and standard Ethernet devices such as vision sensors and wireless routers to be integrated, and has multiple topology possibilities in support of highly scalable and flexible system architectures.



Performance


Reducing overall operating time with high-speed link scan

Min. communication cycle **31.25 μs^{*1}**

High-speed processing **16 \times^{*2} faster**

Link points **2 \times^{*3}**



The advanced protocol built into CC-Link IE TSN is complemented by the time-sharing method functionality that enables simultaneous communications between network stations. This realizes fast communication cycle time of just 31.25 μs^{*1} and high-speed processing 16 times faster than current network performance, resulting in high-speed, highly accurate motion control. Productivity is simultaneously improved owing to a substantial increase in control performance, which reduces overall operating time.



Deterministic control even when mixed with TCP/IP communication TSN Technology

Deterministic performance of cyclic communication is maintained even when mixed with slower information data (non real-time). This enables TCP/IP communication devices to be used without affecting overall control.

* Some devices cannot be connected to CC-Link IE TSN depending on the system configuration.




*1. This value is achieved when fast operation mode of the motion module (RD78GH) is used. For details, please refer to the MELSEC iQ-R Motion Module User's Manual (Application) (IB-0300411ENG).
*2. Comparison with CC-Link IE Field Network Motion
*3. Comparison with CC-Link IE Field Network
*4. Class B managed Ethernet switch supporting CC-Link IE TSN recommended by the CC-Link Partner Association

Optimum control when mixing devices with different communication cycles

Communication cycle 3 set points

TSN Technology

High-speed communication devices ideal for high-speed, highly accurate control and slower response devices ideal for monitoring can be connected using the same line by separating the communication cycle according to speed. This can maximize productivity by using optimum communication cycles based on device performance, such as device stations that require high-speed control and status monitoring stations that operate at lower communication speeds.




Realize high-accuracy synchronous control

Synchronization accuracy $\pm 1 \mu\text{s}$

Max. number of synchronized axes: 256 axes


TSN Technology

Servo amplifier and other device stations can be connected on the same network, enabling synchronous motion control between servo motors and device stations.




Easier parameter setting with imported device profiles (CSP+) Easy startup

Importing profiles (CSP+) describing device features into the engineering software GX Works3 realizes centralized management of connected devices including partner products. Different settings per connected device can be easily done in the same setting procedure.



Easier troubleshooting reduces downtime Easy diagnostics

The location of a cable disconnection and error can be quickly found by visualizing the CC-Link IE TSN network system image in order of connection using the engineering software GX Works3. Since diagnosis information can be checked in real time, a network error due to an unexpected wiring change and module setting change can be quickly found, reducing downtime.






Intelligence

Auto-generation of network parameters Easy startup


Automatic generation of system parameters is relatively easy; simply connect the engineering software with the network master station. New parameters are reflected automatically even when the system configuration changes, reducing overall network setup time.



Easy diagnostics/data collection utilizing general Ethernet technology

Easy diagnostics Data collection

General Ethernet diagnostics software compatible with SNMP*1 can be used for monitoring CC-Link IE TSN and Ethernet network devices. In addition to Mitsubishi Electric's engineering software, system-wide diagnostic analysis and monitoring across the entire network are possible. CC-Link IE TSN communication software for Windows® realizes data collection at a low cost with easy setting without requiring network configuration setting change.



*1. SNMP: Simple Network Management Protocol

Features

System configuration

Master stations

Drives/GOT (HMI)

Block-type remote modules

Managed Ethernet switch/bridge module

Partner products


Development kit/tool

Error cause analysis with highly precise time synchronization

SoE

TSN Technology


Highly accurate time synchronization accuracy within $\pm 1\mu\text{s}$ and each station connected to the network sharing time stamp information in 1 ms units improves system diagnostics and troubleshooting by enabling sequential analysis of stations in the network. The error history is displayed consecutively based on time stamp data, enabling accurate analysis of the cause of error using the actual time the event occurred.



Combining with safety communications


Safety communication

CC-Link IE TSN enables control of safety and non-safety communications realizing a flexible system whereby safety communications can be easily incorporated into the main control network. Safety sub-functions (STO/SS1/SS2/SOS/SLS/SBC/SSM)*1 are also supported for drive-control devices that are on the network.



Ensure latest functional version with firmware update

CC-Link IE TSN-compatible devices can be updated, ensuring latest functional version modules.



*1. Inverter FR-E800-SCE supports only STO/SS1/ SLS/SSM/SBC. Robot MELFA FR Series supports STO/SS1/SS2/SOS/SLS/SLP.

*2. When mixing 100 Mbps with 1 Gbps-rated devices on the same network, connect the 100 Mbps device after a device supporting 1 Gbps (class B).

*3. To obtain the CC-Link IE TSN Firmware Update Tool and relevant firmware update files, please contact your local Mitsubishi Electric sales office or representative.




Connectivity

Combining real-time control and TCP/IP communication

Standard Ethernet Utilize TSN technology Mixed communications


TSN Technology

Supporting standard Ethernet enables various network-compatible devices and diagnostic software to be used, realizing an integrated network infrastructure that is easy to maintain. Ethernet communications supporting TCP/IP communication such as information that has been collected and analyzed by edge devices and IT systems can be mixed in the same line with the real-time control communications of CC-Link IE TSN.



Easy replacement of remote devices Shorter startup

Network station parameters that are stored in the CPU module are automatically distributed to remote devices when initializing the network and when returning disconnected stations to the network. Individual registration of the parameters to each station is unnecessary after replacing remote devices.



Features

System configuration

Master stations

Drives/GOT (HMI)

Block-type remote modules

Managed Ethernet switch/bridge module


Partner products

Development kit/tool


Flexible system configuration with multiple topologies Flexible system

Line, star, and ring topologies are supported, allowing a flexible system configuration. Use line topology for high-speed, high-performance control. This is realized when a system is configured with CC-Link IE TSN-compatible device stations only without additional branch lines. Choose a star topology if a more flexible system configuration is needed. Using Ethernet switches, device stations can be easily distributed to achieve the desired system configuration. Ring topology is ideal for systems requiring high reliability. Data communications continue with normal stations even if a cable is disconnected or an error occurs on a device station via multi-directional communication.


■ Line topology



■ Star topology




■ Ring topology




Integrate other network devices

Adding the CC-Link IE TSN Plus master/local module (RJ71GN11-EIP) to the CC-Link IE TSN system enables utilization of EtherNet/IP™ devices. One port can be connected to the CC-Link IE TSN network, whilst the other port can be connected to the EtherNet/IP™ network. Even if both networks are used simultaneously, functions similar to the CC-Link IE TSN master/local module can be used without affecting the CC-Link IE TSN communication performance. Both networks are easily settable within GX Works3.



Visualization of sensors and space-saving Sensor connection (iQSS)

The AnyWireASLINK bridge module integrates AnyWireASLINK compatible sensors via CC-Link IE TSN. Settings and diagnosis of AnyWireASLINK compatible sensors are easily done from GX Works3 by connecting to a programmable controller via a network.



Selecting module on the system configuration diagram displays monitor information window

Highly scalable system utilizing best-in-class devices Various devices


Supports implementation of high-performance devices realized with a dedicated ASIC/FPGA, and low-cost devices using a software protocol stack on a standard Ethernet chip.



Item	Configuration 1	Configuration 2	Configuration 3	Configuration 4
System configuration	Hardware ^{*1} master Hardware ^{*1} remote	Software ^{*2} master Hardware ^{*1} remote	Hardware ^{*1} master Software ^{*2} remote	Software ^{*2} master Software ^{*2} remote
Transmission speed				
1 Gbps	●	●	●	●
100 Mbps	●	●	●	●

*1. Hardware master/remote: Development with dedicated LSI (ASIC, FPGA)
*2. Software master/remote: Development with software protocol stack (standard Ethernet chip)

System configuration




Flexible IIoT system configuration


CC-Link IE TSN utilizes TSN technology together with its support of TCP/IP communications enables mixing of information communication (non real-time) with Ethernet communication devices. This allows TCP/IP communication devices to be used without affecting real-time deterministic communications, thereby giving greater flexibility when connecting machines and equipment.

Increased productivity

Improved communication performance enables shorter production cycle time. Compared to current systems, adding further control axes and remote I/Os is much easier. In addition, optimum communication cycle times can be realized by supporting both high-speed and low-speed cycle communications according to device specifications.



CC-Link IE TSN



Reduce startup, engineering and maintenance costs

Through its support of SNMP, general Ethernet diagnostics software can be used to identify the network-related errors of CC-Link IE TSN and Ethernet devices more easily. The internal clocks of devices can be synchronized to within the microsecond, making it possible to log historical events in sequence and easily identify the cause of an error.

Various development methods available supporting different products

Product development for CC-Link IE TSN partner product vendors is relatively simple since various options are available. These include a dedicated ASIC/FPGA option for devices that require high performance, and a software protocol stack suitable for lower cost devices that can utilize a general Ethernet chip for network implementation.

Master stations



- Enables mixing of control and TCP/IP communications
- Automatically detects devices on the network, enabling easy network configuration
- Flexible system configuration with integrated safety communication
- Supports various types of motion control
- Highly scalable motion control modules based on the application
- Motion control software embedded in IPCs realizes CC-Link IE TSN-compatible motion control systems
- IPCs based on application requirements with motion control software contribute to high system flexibility

MELSEC iQ-R/iQ-F Series master/local modules can be used as CC-Link IE TSN master/local stations. By supporting the simultaneous use of real-time motion control communication and TCP/IP communication, CC-Link IE TSN performance and functionality are maximized. Motion modules also allow the use of multiple control functions, such as synchronization, cam, speed, and torque control using PLCopen® Motion Control function blocks. The ability to embed motion control software in industrial computers has enabled the realization of CC-Link IE TSN-compatible motion control systems.

Master/local module

RJ71GN11-T2 RJ71GN11-EIP **NEW** FX5-CCLGN-MS

Network management module maximizes CC-Link IE TSN performance and functionality

- Can be used as a CC-Link IE TSN master or local station
- Enables mixing of real-time control communication and TCP/IP communication
- Automatic detection of network devices and parameter distribution realizes easy network configuration
- RJ71GN11-T2 can be used as a safety master or local station when paired with the MELSEC iQ-R Series safety CPU
- RJ71GN11-T2 and RJ71GN11-EIP can control servo motors by using the profile mode of servo amplifiers
- RJ71GN11-EIP can connect CC-Link IE TSN devices to port 1 and EtherNet/IP™ devices to port 2 without affecting CC-Link IE TSN communication performance



Motion module

RD78G RD78GH FX5-□SSC-G

Unlock new system capabilities together with CC-Link IE TSN

- PLCopen® Motion Control function blocks can easily perform various motion control functions such as, positioning, synchronization, cam, speed, and torque control
- Advanced motion control system realized by mixing servo amplifiers and I/O modules on one network
- Supports safety communication when paired with the MELSEC iQ-R Series safety CPU
- The existing projects of the MELSEC iQ-F Series simple motion module (previous model) can be reused
- Operation mode of RD78G can be selected between “Simple Motion mode” and “PLCopen® motion control FB mode” considering the programming language and project



Motion control software

SWM-G

Create new value together in a PC-based environment

- Supports a CC-Link IE TSN servo control system where RTX64 (real-time extension) is installed on a PC (RTX64 is included with SWM-G)
- Meets various application needs by offering various types of motion control, such as positioning, synchronous, cam, speed, and torque control using API libraries
- Utilizes network control to connect and set various remote devices (remote I/O modules, etc.) and TCP/IP devices



Features

System configuration

Master stations

Drives/GOT (HMI)

Block-type remote modules

Managed Ethernet switch/ Bridge module

Partner products

Development kit/tool

Drives/GOT (HMI)



- Quick tuning function for servo amplifiers controls vibration and suppresses overshoot within 0.3 s
- Machine diagnosis of mechanical parts (ball screws, linear guides, belts, and gears) improves predictive maintenance
- High-speed communication together with high-performance inverter improves productivity
- Robots can realize advanced operations by combining force and vision sensors
- Remote system-wide monitoring enabled using GOT Mobile function
- Various sample screens available, enabling the visualization of network device statuses from the GOT (HMI)

Drive products such as servos, inverters, and robots, together with GOT (HMI) all support CC-Link IE TSN. The MELSERVO-J5 Series servo amplifiers, when combined with motion modules, realize highly accurate motion control that contributes to the performance of smart factory production systems. The Inverter A800/E800 Series is equipped with CC-Link IE TSN, enabling real-time collection of production data, and the robot MELFA FR Series and the GOT2000 Series HMI, which enhance coordination with automation devices, thereby improving productivity and efficiency.

AC servo MELSERVO-J5/MELSERVO-JET Series

MR-J5-G MR-J5W-G MR-J5-G-RJ MR-J5D-G4
MR-JET-G

Next generation MELSERVO-J5/MELSERVO-JET Series improves production systems

- Highly accurate synchronous control when combined with a motion module
- Multi-axis servo amplifier and drive unit are also available
- MR-J5-G-RJ/MR-J5D-G4 which are compatible with safety communications support safety sub-functions STO/SS1/SS2/SOS/SBC/SLS/SSM/SDI/SLI/SLT



MR-J5-G MR-J5W3-G MR-J5D3-G4 MR-JET-G

Inverter A800/E800 Series

FR-A800-GN FR-E800-E/SCE

Industry-leading high performance and quality

- Shop floor data collection in real-time using either 1 Gbps*1/100 Mbps communications speed
- Enables mixing of real-time control communication and TCP/IP communication
- FR-E800-SCE which is compatible with safety communications supports safety sub-functions STO/SS1/SLS/SBC/SSM

*1. 1 Gbps will be supported in the future by FR-E800-E/SCE with option.



FR-A800-GN

FR-E800-SCE

Industrial robot MELFA FR Series controller

CR800-R

iQ Platform compatible controller

- Seamlessly integrates the various controllers used in a production site with HMIs, the engineering environment and the network
- Multi-CPU configuration dramatically improves its interaction with FA equipment, offering highly precise control and fast yet simple information management
- Safety devices connected with the safety remote modules of the safety programmable controllers can be used via the CC-Link IE TSN master and local modules



HMI GOT2000 Series CC-Link IE TSN communication unit

GT25-J71GN13-T2

■ Improves productivity and efficiency through advanced visualization of production equipment

- CC-Link IE TSN-compatible GOT (HMI) communication unit
- Use as a CC-Link IE TSN local station
- GT27 and GT25*¹ are supported

*1. GT2505, GT2512-WX, GT2510-WX, GT2507-W, GT2507T, GT2506HS, and GT2505HS are not supported.



Block-type remote modules



- Easily set parameters using only hardware switches*1
- Detection of low power supply voltage
- Spring-clamp terminal block reduces wiring
- Input module conforms to IEC 61131-2 Type3 (digital input standard operation range), supporting various sensors*1
- Switch to CC-Link IE Field Network device station mode*1
- Block-type remote module with safety function enables safety control
- Input/output timing can be synchronized with inter-modular synchronization cycle, enabling highly accurate control of the system*1



Block-type remote modules are recognized as device stations on the CC-Link IE TSN. They are mainly used when installation requires them to be close to connected I/Os to save on wiring. Digital I/O modules are the sensors of the automation system and can be easily connected to switches, indicator lamps, sensors, and other devices. Analog modules can be connected to devices that process varying voltages and current signals. The combination of a block-type remote module with safety function and safety CPU realizes safety network communications.

Easier system startup*1

The IP address for each module can be set easily using the switches on the front of the module. Additional functions can be set using switches as well, without requiring dedicated engineering software.

Switch to CC-Link IE Field Network device station mode*1

Setting the switches on the front of the module enables to be used as either a CC-Link IE TSN or CC-Link IE Field Network device station without requiring separate modules.



*1. Block-type safety remote I/O modules are not supported.

Input module

- Response time can be set at 0 ms, 0.2 ms, 1 ms, 1.5 ms, 5 ms, 10 ms, 20 ms and 70 ms (initial setting is 1 ms)
- Input ON/OFF voltage and current comply with IEC 61131-2 (digital input standard operating range) Type3, supporting various sensors
- Functions can be easily setup from the front of the module using switches, without requiring dedicated engineering software

Spring-clamp terminal block

NZ2GN2S1-16D

NZ2GN2S1-32D



NZ2GN2S1-32D

Model	Input type DC input	Input points	Rated input voltage/current	Wiring type
NZ2GN2S1-16D	Positive common Negative common	16 points	24 V DC (6.6 mA)	1-wire
NZ2GN2S1-32D	Positive common Negative common	32 points	24 V DC (6 mA)	1-wire

Screw terminal block

NZ2GN2B1-16D

NZ2GN2B1-32D



NZ2GN2B1-32D

Model	Input type DC input	Input points	Rated input voltage/current	Wiring type
NZ2GN2B1-16D	Positive common Negative common	16 points	24 V DC (6.6 mA)	1-wire
NZ2GN2B1-32D	Positive common Negative common	32 points	24 V DC (6 mA)	1-wire

Sensor connector (e-CON)

NZ2GNCE3-32D



Model	Input type DC input	Input points	Rated input voltage/current	Wiring type
NZ2GNCE3-32D	Positive common	32 points	24 V DC (6.6 mA)	3-wire

40-pin connector

NZ2GNCF1-32D



Model	Input type DC input	Input points	Rated input voltage/current	Wiring type
NZ2GNCF1-32D	Positive common Negative common	32 points	24 V DC (6.6 mA)	1-wire

Output module

- Select either to hold or clear the output value when disconnected from the data link or when the master stations programmable controller CPU has stopped
- Prevents module malfunction using the output overload and overheat protection function
- Functions can be easily setup from the front of the module using switches, without requiring dedicated engineering software

Spring-clamp terminal block

NZ2GN2S1-16T
 NZ2GN2S1-16TE
 NZ2GN2S1-32T
 NZ2GN2S1-32TE



NZ2GN2S1-32T

Model	Output type Transistor output	Output points	Rated load voltage/Max. load current	Wiring type
NZ2GN2S1-16T	Sink	16 points	12/24 V DC (0.5 A)	1-wire
NZ2GN2S1-16TE	Source	16 points	12/24 V DC (0.5 A)	1-wire
NZ2GN2S1-32T	Sink	32 points	12/24 V DC (0.5 A)	1-wire
NZ2GN2S1-32TE	Source	32 points	12/24 V DC (0.5 A)	1-wire

Screw terminal block

NZ2GN2B1-16T
 NZ2GN2B1-16TE
 NZ2GN2B1-32T
 NZ2GN2B1-32TE



NZ2GN2B1-32T

Model	Output type Transistor output	Output points	Rated load voltage/Max. load current	Wiring type
NZ2GN2B1-16T	Sink	16 points	12/24 V DC (0.5 A)	1-wire
NZ2GN2B1-16TE	Source	16 points	12/24 V DC (0.5 A)	1-wire
NZ2GN2B1-32T	Sink	32 points	12/24 V DC (0.5 A)	1-wire
NZ2GN2B1-32TE	Source	32 points	12/24 V DC (0.5 A)	1-wire

40-pin connector

NZ2GNCF1-32T



Model	Output type Transistor output	Output points	Rated load voltage/Max. load current	Wiring type
NZ2GNCF1-32T	Sink	32 points	12/24 V DC (0.1 A)	1-wire

I/O combined module

- Combined I/O modules include both input module and output module functions
- Response time can be set at 0 ms, 0.2 ms, 1 ms, 1.5 ms, 5 ms, 10 ms, 20 ms, and 70 ms (initial setting is 1 ms)
- Input ON/OFF voltage and current comply with IEC 61131-2 (digital input standard operating range) Type3, supporting various sensors
- Select either to hold or clear the output value when disconnected from the data link or when the master station's programmable controller CPU has stopped
- Prevents module malfunction using the output overload and overheat protection function
- Functions can be easily setup from the front of the module using switches, without requiring dedicated engineering software

Spring-clamp terminal block

NZ2GN2S1-32DT NZ2GN2S1-32DTE



NZ2GN2S1-32DT

Model	Input type DC input	Input points	Rated input voltage/ current	Output type Transistor output	Output points	Rated load voltage/ Max. load current	Wiring type
NZ2GN2S1-32DT	Positive common	16 points	24 V DC (6 mA)	Sink	16 points	24 V DC (0.5 A)	1-wire
NZ2GN2S1-32DTE	Negative common	16 points	24 V DC (6 mA)	Source	16 points	24 V DC (0.5 A)	1-wire

Screw terminal block

NZ2GN2B1-32DT NZ2GN2B1-32DTE



NZ2GN2B1-32DT

Model	Input type DC input	Input points	Rated input voltage/ current	Output type Transistor output	Output points	Rated load voltage/ Max. load current	Wiring type
NZ2GN2B1-32DT	Positive common	16 points	24 V DC (6 mA)	Sink	16 points	24 V DC (0.5 A)	1-wire
NZ2GN2B1-32DTE	Negative common	16 points	24 V DC (6 mA)	Source	16 points	24 V DC (0.5 A)	1-wire

Sensor connector (e-CON)

NZ2GNCE3-32DT



Model	Input type DC input	Input points	Rated input voltage/ current	Output type Transistor output	Output points	Rated load voltage/ Max. load current	Wiring type
NZ2GNCE3-32DT	Positive common	16 points	24 V DC (6.6 mA)	Sink	16 points	24 V DC (0.5 A)	3-wire

■ Analog input module

- 200 µs/channel analog input module conversion speed
- Functions can be easily setup from the front of the module using switches, without requiring dedicated engineering software

Spring-clamp terminal block NZ2GN2S-60AD4



Model	Input type	Number of channels
NZ2GN2S-60AD4	Analog voltage/current input	4

Screw terminal block NZ2GN2B-60AD4



Model	Input type	Number of channels
NZ2GN2B-60AD4	Analog voltage/current input	4

■ Analog output module

- 200 µs/channel analog output module conversion speed
- Functions can be easily setup from the front of the module using switches, without requiring dedicated engineering software

Spring-clamp terminal block NZ2GN2S-60DA4



Model	Output type	Number of channels
NZ2GN2S-60DA4	Analog voltage/current output	4

Screw terminal block NZ2GN2B-60DA4



Model	Output type	Number of channels
NZ2GN2B-60DA4	Analog voltage/current output	4

Waterproof/dustproof type (IP67) remote module

- Complies with IP67 rating. A control panel is no longer necessary, saving on hardware cost and space



NZ2GN12A42-16DT

Input module

- Response time can be set at 0 ms, 0.2 ms, 1 ms, 1.5 ms, 5 ms, 10 ms, 20 ms and 70 ms

Waterproof connector (screw lock)

NZ2GN12A4-16D NZ2GN12A4-16DE

Model	Input type DC input	Input points	Rated input voltage/current	Wiring type
NZ2GN12A4-16D	Positive common	16 points	24 V DC (7.3 mA)	2- to 4-wire
NZ2GN12A4-16DE	Negative common	16 points	24 V DC (7.3 mA)	2- to 4-wire

Output module

- Since the maximum load current is 4 A/point, a large load can be connected

Waterproof connector (screw lock)

NZ2GN12A2-16T NZ2GN12A2-16TE

Model	Output type Transistor output	Output points	Rated load voltage/ Max. load current	Wiring type
NZ2GN12A2-16T	Sink	16 points	12/24 V DC (2 A, 4 A)	2-wire
NZ2GN12A2-16TE	Source	16 points	12/24 V DC (2 A, 4 A)	2-wire

I/O combined module

- The I/O combined module controls both inputs and outputs all in one module
- Response time can be set at 0 ms, 0.2 ms, 1 ms, 1.5 ms, 5 ms, 10 ms, 20 ms and 70 ms
- Since the maximum load current is 4 A/point, a large load can be connected

Waterproof connector (screw lock)

NZ2GN12A42-16DT NZ2GN12A42-16DTE

Model	Input type DC input	Input points	Rated input voltage/ current	Output type Transistor output	Output points	Rated load voltage/ Max. load current	Wiring type
NZ2GN12A42-16DT	Positive common	8 points	24 V DC (7.3 mA)	Sink	8 points	12/24 V DC (2 A, 4 A)	2- to 4-wire (input) 2-wire (output)
NZ2GN12A42-16DTE	Negative common	8 points	24 V DC (7.3 mA)	Source	8 points	12/24 V DC (2 A, 4 A)	2- to 4-wire (input) 2-wire (output)

Block-type remote module with safety functions

- Remote I/O modules that support safety functions
- Performs safety control when used together with the MELSEC iQ-R Series Safety CPU

Input module

- Input module with safety functions
- Single or double wiring can be selected per input point
- Compliant with international safety standards, ISO 13849-1 Category 4 PL e and IEC 61508 SIL 3

Spring-clamp terminal block NZ2GNSS2-8D



Model	Input type DC input	Input points	Rated input voltage/current	Wiring type
NZ2GNSS2-8D	Negative common	Single wiring: 8 points Double wiring: 4 points	24 V DC (7.3 mA)	2-wire

Output module

- Output module with safety functions
- Single or double wiring can be selected per output point
- Compliant with international safety standards, ISO 13849-1 Category 4 PL e and IEC 61508 SIL 3

Spring-clamp terminal block NZ2GNSS2-8TE



Model	Output type Transistor output	Output points	Rated load voltage/Max. load current	Wiring type
NZ2GNSS2-8TE	Source + source	Single wiring: 8 points Double wiring: 4 points	24 V DC (0.5 A)	2-wire

I/O combined module

- I/O combined module with safety functions
- Single or double wiring can be selected per input and output point
- Compliant with international safety standards, ISO 13849-1 Category 4 PL e and IEC 61508 SIL 3
- Embedded fast logic function enables control of safety logic from within the remote module. High-speed control (response speed: 5.8 ms*1) is realized without being affected by the safety CPU or network

*1. Depends on the parameter settings.

Spring-clamp terminal block NZ2GNSS2-16DTE



Model	Input type DC input	Input points	Rated input voltage/ current	Output type Transistor output	Output points	Rated load voltage/ Max. load current	Wiring type
NZ2GNSS2-16DTE	Negative common	Single wiring: 8 points Double wiring: 4 points	24 V DC (7.3 mA)	Source + source	Single wiring: 8 points Double wiring: 4 points	24 V DC (0.5 A)	2-wire

Managed Ethernet switch/ bridge module

Managed Ethernet switch

NZ2MHG-TSNT8F2 Class B

- Star topology can be configured with a managed Ethernet switch (8 ports)
 - TCP/IP communication devices can be connected to empty Ethernet ports, enabling a highly-flexible advanced system
 - Disruptions to the control system are kept to a minimum when an error occurs such as remote device failure and a cable disconnection
 - Wiring distance between devices can be shortened, thereby reducing wiring cost.
- In addition, layout modification and addition/replacement of remote devices can be efficiently completed



This product was developed and manufactured by Moxa Inc.
Please note that the specifications and guarantee conditions of the products are different from the MELSEC Series products.

Bridge module

CC-Link IE TSN-AnyWireASLINK bridge module*1

NZ2AW1GNAL

- Seamlessly integrates AnyWireASLINK products into CC-Link IE TSN
- AnyWireASLINK is a reduced wiring network realizing monitoring of sensors and reduced installation space
- Supports iQSS (iQ Sensor Solution), which enables parameter setup and monitoring of AnyWireASLINK products



*1. For further details, please refer to "DIGITAL LINK SENSOR AnyWireASLINK catalog (L(NA)08221E)".

Mitsubishi Electric System & Service

For details of Mitsubishi Electric System & Service Co., Ltd. products, please contact us via email.
 <Sales office> OVERSEAS SERVICE SECTION mail: osb.webmaster@melsc.jp

Industrial switching hub

DT135TXA Class A

- Compatible with 10 Mbps/100 Mbps/1 Gbps transmission speed
- Compact size unit with 5 ports
- Supports 12 V DC up to 48 V DC wide voltage-range. Two power supply inputs (redundant power supply) are also possible
- Supports the line, star, line and star combination network topologies
- Complies with UL/CE/FCC standards enabling export to Europe and North America



Ethernet cable

SC-E5EW Series NEW

- 1000BASE-T Standard compliant. This Ethernet cable with double shield has an outstanding shield performance
- Available in lengths from 1 m to 100 m (in 1 m increments). For using in indoor movable area, available lengths are from 1 m to 45 m. Available in lengths less than 1 m also



Item	SC-E5EW-S□M*1	SC-E5EW-S□M-MV*2	SC-E5EW-S□M-L*3
Cable type	Category 5e or higher, (double shielded/STP) straight cable		
Number of core wires	8 wires (4 twisted pairs)		
Double shield	Aluminum/polyester tape, tin-plated annealed copper wire braid		
Installation environment	Indoor	Indoor movable	Indoor/outdoor
Finished outside diameter	Flame retardant PVC, 6.8 mm	Flame retardant PVC, 6.5 mm	LAP sheath, 10 mm
Connector	RJ-45 connector with shield, straight connection		
Conforming standards	IEEE802.3 1000BASE-T ANSI/TIA/EIA-568-B (Category 5e) ISO/IEC 11801		

*1. "□" in the model name denotes a cable length (0.5 m, from 1 m up to 100 m in 1 m increments).
 *2. "□" in the model name denotes a cable length (0.1 m, 0.2 m, 0.3 m, 0.5 m, from 1 m up to 45 m in 1 m increments).
 *3. "□" in the model name denotes a cable length (from 1 m up to 100 m in 1 m increments).

Inline coupler

SPAD-RJ45S-E5E NEW

- 8 conductor RJ-45 female to female, shielded, fits standard type Keystone Wall Plate
- Can be used in patch panels, wall jacks, or to extend cable lengths



Item	Specifications
Adaptable connector	RJ-45 connector with shield
Operable temperature	-10...60°C
Conforming standards	IEEE 802.3 1000BASE-T ANSI/TIA/EIA-568-B (Category 5e) ISO/IEC 11801



For further inquiries concerning partner and CC-Link IE TSN products and development of supported products, please contact CLPA.



www.cc-link.org

For further details, please refer to the "Open Field Network CC-Link Family Compatible Product Development Guidebook (L(NA)08052E)".



Development kit

Dedicated communication LSI CP610

- CC-Link IE TSN master station/local station can be developed without considering protocols
- Allows selection of MPU and OS freely. Customized sample codes according to hardware specifications and applications can be provided
- Parameter settings and diagnosis of the CC-Link IE TSN master station/local station can be done using the CC-Link IE TSN setting tool included in the source code development kit
- Provides SPICE model for PCI Express® interface and IBIS model for other interfaces as a transmission simulation model*1




*1. Confidentiality agreement needs to be signed to provide SPICE model and IBIS model. Please consult with your local Mitsubishi Electric sales office.

Master station software development kit (SDK)

- Various systems can be configured using the software protocol stack irrespective of computers specifications
- API compliance with CANopen® makes it easy for developers of CANopen®-compatible products to develop CC-Link IE TSN-compatible products
- Source code package can be customized, enabling function expansion and porting to different development environments
- Kit with library allows system configuration at a lower cost
- Embedded functions improve devices by utilizing features such as mixing TCP/IP communication




*2. SW1DTD-GNSDK1M
*3. SW1DTD-GNSDK2M



■ Communication LSI embedded with GbE-PHY CP620

- CC-Link IE TSN remote station can be developed without considering protocols
- Embedded GbE-PHY enables easier communication circuit pattern development with fewer peripheral parts and circuits required around the CPU and GbE-PHY, thereby reducing board size
- Customized sample codes according to hardware specifications and applications can be provided
- Embedded hardware RTOS*1 reduces CPU load and power consumption


*1. RTOS: Real-time operating system



■ Sample code for class A remote station (provided by CC-Link Partner Association)

- Devices supporting CC-Link IE TSN can be developed just by implementing software protocol stack in devices equipped with Ethernet interface
- Use sample code for CC-Link IE TSN class A remote station


Download sample code from the CC-Link Partner Association website below.
https://www.cc-link.org/en/cclink/cclinkie/code_cclinkie_tsn.html



Tool

■ CC-Link IE TSN communication software for Windows® (CC-Link IE TSN data collector enclosed)

- Easily collects accurate control data of CC-Link IE TSN devices
- Collected data from the function library can be utilized for data analysis and monitoring
- Realizes accurate data analysis by collection of control data with time stamp
- Reduces configuration cost for realizing a simple data collection system as setup is straightforward utilizing computer-based software
- CC-Link IE TSN data collector enables integration with Edgecross



General specifications

The following table provides the environmental specifications required for using the CC-Link IE TSN master/local module and block-type modules listed in this catalog. For the environmental specifications required to use other products, please refer to the relevant product catalog or manual.

Item	MELSEC iQ-R Series master/local module Block-type remote module	MELSEC iQ-F Series master/local module
Operating ambient temperature	0...55°C ^{*1}	-20...55°C, non-freezing ^{*2*3}
Storage ambient temperature		-25...75°C
Operating ambient humidity		5...95% RH, non-condensing
Storage ambient humidity		
Vibration resistance	Please refer to the relevant product manual	
Shock resistance	Compliant with JIS B 3502 and IEC 61131-2 (147 m/s ² , 3 times each in directions X, Y, and Z)	147 m/s ² , Action time: 11 ms, 3 times each in directions X, Y, and Z by half-sine pulse ^{*4}
Operating atmosphere	No corrosive gases ^{*5} , no flammable gases, no excessive conductive dust	
Operating altitude ^{*6}		0...2000 m ^{*7}
Installation location	Inside a control panel	
Overvoltage category ^{*8}		≤ II
Pollution level ^{*9}		≤ 2

*1. Enables standard MELSEC iQ-R Series modules to support extended operating ambient temperature of 0 to 60°C, ensuring the same performance as the standard operating ambient temperature (0 to 55°C). When requiring to use in an ambient temperature environment higher than 60°C, please consult your local Mitsubishi Electric representative.

*2. In the case where operating ambient temperature is lower than 0°C, the specifications are different from the above description. For details, please refer to the "MELSEC iQ-F FX5U User's Manual (Hardware)".

*3. When using FX5-CCLGN-MS manufactured in December 2020 or earlier, the operating ambient temperature is -20 to 50°C. The operating ambient temperature of the programmable controller system is the same.

*4. The criterion is shown in IEC 61131-2.

*5. For RJ71GN11-T2 and RJ71GN11-EIP, the special coated product, which meets the regulation (IEC 60721-3-3: 1994 3C2) related to corrosive gas, is available for the use in a corrosive gas environment. For details of the special coated product, please consult your local Mitsubishi Electric representative.

*6. Do not use or store the programmable controller under pressure higher than the atmospheric pressure of altitude 0 m. Doing so may cause malfunction or lead to failure.

*7. When using programmable controllers at an altitude higher than 2000 m, the upper limits of the permissible voltage and the operating ambient temperature become lower. For further details, please refer to the technical bulletin "FA-A-0152" for the MELSEC iQ-R Series and "HIME-T-P-0185" for the MELSEC iQ-F Series.

*8. This indicates the section of the power supply to which the equipment is assumed to be connected between the public electrical power distribution network and the machinery within premises. Category II applies to equipment for which electrical power is supplied from fixed facilities. The surge voltage withstand level for up to the rated voltage of 300 V is 2500 V.

*9. This index indicates the degree to which conductive material is generated in terms of the environment in which the equipment is used. Pollution level 2 is when only non-conductive pollution occurs. Temporary conductivity caused by condensation must be expected occasionally.

Performance specifications

Item	MELSEC iQ-R Series master/local module RJ71GN11-T2	MELSEC iQ-R Series CC-Link IE TSN Plus master/local module RJ71GN11-EIP NEW	MELSEC iQ-F Series master/local module FX5-CCLGN-MS*1	MELSEC iQ-R Series motion module RD78G□/GH□	MELSEC iQ-F Series motion module FX5-□SSC-G
Communication speed (bps)	1 G/100 M	1 G/100 M	1 G	1 G/100 M*2	1 G
Maximum stations per network*3	121	121	61 (master station)	121	21 (FX5-40SSC-G) 25 (FX5-80SSC-G)
Connection cable	Ethernet cable (Category 5e or higher)	Ethernet cable (Category 5e or higher)	Ethernet cable (Category 5e or higher)	Ethernet cable (Category 5e or higher)	Ethernet cable (Category 5e or higher)
Overall cable distance (m)	Line: 12000 Ring: 12100 Others: Depends on system configuration	Line: 12000 Others: Depends on system configuration	Line: 6000 (master station) Others: Depends on system configuration	Line: 12000	Line: 2000 (FX5-40SSC-G) Line: 2400 (FX5-80SSC-G) Others: Depends on system configuration
Maximum station-to-station distance (m)	100	100	100	100	100
Maximum number of networks	239	239	239	239	239
Network topology*4	Line, star*5, ring	Line*6, star*5	Line, star*5	Line, star*5	Line, star*5
Communication method	Time-sharing method	Time-sharing method	Time-sharing method	Time-sharing method	Time-sharing method
Maximum link points per network					
RX/RV	16384 points, 2K bytes	16384 points, 2K bytes	8192 points, 1K bytes (master station)	16384 points, 2K bytes	8192 points, 1K bytes
RW/RVw	8192 points, 16K bytes	8192 points, 16K bytes	4096 points, 8K bytes (master station)	8192 points, 16K bytes	1024 points, 2K bytes
LB	32768 points, 4K bytes	32768 points, 4K bytes	-	-	-
LW	16384 points, 32K bytes	16384 points, 32K bytes	-	-	-
Maximum link points per station					
RX/RV	16384 points, 2K bytes	16384 points, 2K bytes	8192 points, 1K bytes (master station)	16384 points, 2K bytes	8192 points, 1K bytes
RW/RVw	8192 points, 16K bytes	8192 points, 16K bytes	4096 points, 8K bytes (master station)	8192 points, 16K bytes	1024 points, 2K bytes
LB	32768 points, 4K bytes	32768 points, 4K bytes	-	-	-
LW	16384 points, 32K bytes	16384 points, 32K bytes	-	-	-
Safety communications					
Maximum number of safety connections per station	120 connections	-	-	120 connections	-
Maximum number of link points per safety connection (word)	8 (input: 8, output: 8)	-	-	8 (input: 8, output: 8)	-
Transient transmission capacity					
Transient transmission capacity (byte)	1920 maximum	1920 maximum	1920 maximum	1920 maximum	1920 maximum
EtherNet/IP™ communications					
Data transmission speed (bps)					
	-	1 G/100 M	-	-	-
Class1 communications	Number of connections	-	<ul style="list-style-type: none"> Instance communications: 256*7 Tag communications: 256*7 	-	-
	Communication data size (byte)	-	1444 (per connection)*8	-	-
	RPI (communication cycle) (ms)	-	0.5...60000 (in increments of 0.5 ms)	-	-
	PPS (communication processing performance)*9 (pps)	-	12000	-	-
UCMM communications	Number of connections (number of simultaneous executions)	-	<ul style="list-style-type: none"> Server: 96*7*10 Client: 32 	-	-
	Communication data size (byte)	-	<ul style="list-style-type: none"> Message communications: 504 (including headers) Tag communications: 498 	-	-
Class3 communications	Number of connections	-	<ul style="list-style-type: none"> Server: 96*7*10 Client: 256*7 	-	-
	Communication data size (byte)	-	<ul style="list-style-type: none"> Message communications: 1404 (per connection) Tag communications: 496 (per connection) 	-	-

*1. For specifications of local station, please refer to the "MELSEC iQ-F FX5 User's Manual (CC-Link IE TSN) (SH-082215ENG)";

*2. System configuration mixing 1 Gbps devices and 100 Mbps devices will be supported in the future.

*3. Includes a master station.

*4. Please use class B managed Ethernet switch supporting CC-Link IE TSN recommended by the CC-Link Partner Association.

*5. Line topology and star topology can be mixed.

*6. The CC-Link IE TSN Plus master/local module can only be connected at the end of the network.

*7. The total number of connections for Class1 communications, UCMM tag communications (server function), and Class3 communications is 256. Therefore, the number of each connection varies depending on the number and size of separate communications.


*8. If the external device does not support Large Forward Open (CIP option specifications), the communication data size is up to 504 bytes.

*9. PPS: Number of frames that can be processed per second

*10. The maximum number of simultaneous executions (the number of connections that can be received simultaneously) for the server function is 96 for the total of UCMM and Class3 communications server functions.

■ Network topologies


■ Line topology



Network topology ideal for system configurations with high-speed/high-performance control

- High-speed communication is possible as the system is configured with CC-Link IE TSN-compatible device stations only
- Easier system configuration without an Ethernet switch
- Ideal for highly accurate motion control systems


■ Star topology



Network topology ideal for flexible system configurations

- Easily realizes distributed arrangement of device stations with an Ethernet switch
- Easy to change/rearrange equipment or system configuration
- Ideal for general production line control systems

■ Ring topology



Network topology ideal for systems requiring high reliability*1


- Maintain data communications with normal stations even if a cable is disconnected or an error occurs in one of the device stations
- Configuration without requiring an Ethernet switch
- Ideal for continuously operating control system

*1. Please refer to the relevant product manual for confirming if ring topology is supported.
Mixing of star topology and line topology is not supported.

■CC-Link IE TSN Class

CC-Link IE TSN certifies nodes and switches to a specific class level according to its functionality and performance classification. Products can be classified as either class A or B. For the CC-Link IE TSN Class of each product, please check the CC-Link Partner Association website or the relevant product catalog or manual. Supported functions and system configuration may differ according to the CC-Link IE TSN Class of products used. For example, products compatible with class B are necessary to configure a high-speed motion control system. For details of configuring systems with both class A and class B devices, please refer to relevant master product manual.

■System configuration



- Synchronous accuracy of a system varies relative to the combination of connected devices and switches
CC-Link IE TSN Class
- Use class B Ethernet switch when configuring a star topology with class B devices
- Use class B devices when configuring a system within $\pm 1 \mu\text{s}$ high-accuracy synchronization, connect class A devices to a separate branch line from class B devices (for details of system configuration, please refer to relevant master product manual)
- Mitsubishi Electric's block type remote modules include modules complying both class B and A.

Extensive global support coverage providing expert help whenever needed

Global FA centers

EMEA

Europe FA Center

MITSUBISHI ELECTRIC EUROPE B.V. Polish Branch
Tel: +48-12-347-65-81

Germany FA Center

MITSUBISHI ELECTRIC EUROPE B.V. German Branch
Tel: +49-2102-486-0 / Fax: +49-2102-486-1120

UK FA Center

MITSUBISHI ELECTRIC EUROPE B.V. UK Branch
Tel: +44-1707-27-8780 / Fax: +44-1707-27-8695

Czech Republic FA Center

MITSUBISHI ELECTRIC EUROPE B.V. Czech Branch
Tel: +420-255 719 200

Italy FA Center

MITSUBISHI ELECTRIC EUROPE B.V. Italian Branch
Tel: +39-039-60531 / Fax: +39-039-6053-312

Russia FA Center

MITSUBISHI ELECTRIC (RUSSIA) LLC ST.
Petersburg Branch
Tel: +7-812-633-3497 / Fax: +7-812-633-3499

Turkey FA Center

MITSUBISHI ELECTRIC TURKEY A.S. Umraniye Branch
Tel: +90-216-526-3990 / Fax: +90-216-526-3995

Asia-Pacific

China

Beijing FA Center

MITSUBISHI ELECTRIC AUTOMATION (CHINA) LTD.
Beijing FA Center
Tel: +86-10-6518-8830 / Fax: +86-10-6518-2938

Guangzhou FA Center

MITSUBISHI ELECTRIC AUTOMATION (CHINA) LTD.
Guangzhou FA Center
Tel: +86-20-8923-6730 / Fax: +86-20-8923-6715

Shanghai FA Center

MITSUBISHI ELECTRIC AUTOMATION (CHINA) LTD.
Shanghai FA Center
Tel: +86-21-2322-3030 / Fax: +86-21-2322-3000

Tianjin FA Center

MITSUBISHI ELECTRIC AUTOMATION (CHINA) LTD.
Tianjin FA Center
Tel: +86-22-2813-1015 / Fax: +86-22-2813-1017

Taiwan

Taipei FA Center

SETSUYO ENTERPRISE CO., LTD.
Tel: +886-2-2299-9917 / Fax: +886-2-2299-9963

Korea

Korea FA Center

MITSUBISHI ELECTRIC AUTOMATION KOREA CO., LTD.
Tel: +82-2-3660-9632 / Fax: +82-2-3664-0475

Thailand

Thailand FA Center

MITSUBISHI ELECTRIC FACTORY AUTOMATION
(THAILAND) CO., LTD.
Tel: +66-2682-6522-31 / Fax: +66-2682-6020

ASEAN

ASEAN FA Center

MITSUBISHI ELECTRIC ASIA PTE. LTD.
Tel: +65-6470-2480 / Fax: +65-6476-7439

Malaysia

Malaysia FA Center

Malaysia FA Center
Tel: +60-3-7626-5080 / Fax: +60-3-7658-3544

Indonesia

Indonesia FA Center

PT. MITSUBISHI ELECTRIC INDONESIA
Cikarang Office
Tel: +62-21-2961-7797 / Fax: +62-21-2961-7794

Vietnam

Hanoi FA Center

MITSUBISHI ELECTRIC VIETNAM COMPANY LIMITED
Hanoi Branch Office
Tel: +84-24-3937-8075 / Fax: +84-24-3937-8076

Ho Chi Minh FA Center

MITSUBISHI ELECTRIC VIETNAM COMPANY LIMITED
Tel: +84-28-3910-5945 / Fax: +84-28-3910-5947

Philippines

Philippines FA Center

MELCO Factory Automation Philippines Inc.
Tel: +63-(0)2-8256-8042

India

India Ahmedabad FA Center

MITSUBISHI ELECTRIC INDIA PVT. LTD.
Ahmedabad Branch
Tel: +91-7965120063

India Bangalore FA Center

MITSUBISHI ELECTRIC INDIA PVT. LTD.
Bangalore Branch
Tel: +91-80-4020-1600 / Fax: +91-80-4020-1699

India Chennai FA Center

MITSUBISHI ELECTRIC INDIA PVT. LTD.
Chennai Branch
Tel: +91-4445548772 / Fax: +91-4445548773

India Coimbatore FA Center

MITSUBISHI ELECTRIC INDIA PVT. LTD.
Coimbatore Branch
Tel: +91-422-438-5606

India Gurgaon FA Center

MITSUBISHI ELECTRIC INDIA PVT. LTD.
Gurgaon Head Office
Tel: +91-124-463-0300 / Fax: +91-124-463-0399

India Pune FA Center

MITSUBISHI ELECTRIC INDIA PVT. LTD.
Pune Branch
Tel: +91-20-2710-2000 / Fax: +91-20-2710-2100

Americas

USA

North America FA Center

MITSUBISHI ELECTRIC AUTOMATION, INC.
Tel: +1-847-478-2469 / Fax: +1-847-478-2253

Mexico

Mexico City FA Center

MITSUBISHI ELECTRIC AUTOMATION, INC.
Mexico Branch
Tel: +52-55-3067-7511

Mexico FA Center

MITSUBISHI ELECTRIC AUTOMATION, INC.
Queretaro Office
Tel: +52-442-153-6014


Mexico Monterrey FA Center

MITSUBISHI ELECTRIC AUTOMATION, INC.
Monterrey Office
Tel: +52-55-3067-7521

Brazil

Brazil FA Center

MITSUBISHI ELECTRIC DO BRASIL COMERCIO E
SERVICOS LTDA.
Tel: +55-11-4689-3000 / Fax: +55-11-4689-3016




CC-Link Partner Association (CLPA) - Actively promoting worldwide adoption of CC-Link networks

Proactively supporting CC-Link, from promotion to specification development

The CC-Link Partner Association (CLPA) was established to promote the worldwide adoption of the CC-Link open-field network. By conducting promotional activities such as organizing trade shows and seminars, conducting conformance tests, and providing catalogs, brochures and website information, CLPA activities are successfully increasing the number of CC-Link partner manufacturers and CC-Link-compatible products. As such, CLPA is playing a major role in the globalization of CC-Link.



Seminar



Trade show



Conformance testing lab

Visit the CLPA website for the latest CC-Link information.



CLPA website
www.cc-link.org




CLPA
Headquarters

6F Ozone Front Bldg. 3-15-58 Ozone
Kita-ku, Nagoya 462-0825, JAPAN
TEL: +81-52-919-1588 FAX: +81-52-916-8655
e-mail: info@cc-link.org

Global influence of CC-Link continues to spread

CC-Link is supported globally by CLPA. With offices throughout the world, support for partner companies can be found locally. Each regional CLPA office undertakes various support and promotional activities to further the influence of CC-Link/CC-Link IE in that part of the world. For companies looking to increase their presence in their local area, CLPA is well placed to assist these efforts through offices in all major regions.

CLPA-Europe **CT**
(Germany)



CT : Conformance testing lab

Discover the latest information in Factory Automation

Factory Automation Global website

Mitsubishi Electric Factory Automation provides a mix of services to support its customers worldwide. A consolidated global website is the main portal, offering a selection of support tools and a window to its local Mitsubishi Electric sales and support network.

From here you can find:

- Overview of available factory automation products
- Library of downloadable literature
- Support tools such as online e-learning courses, terminology dictionary, etc.
- Global sales and service network portal
- Latest news related to Mitsubishi Electric factory automation

Mitsubishi Electric Factory Automation
Global website:
www.MitsubishiElectric.com/fa



Online e-learning

An extensive library of e-learning courses covering the factory automation product range has been prepared. Courses from beginner to advanced levels of difficulty are available in various languages.



Beginner level

Designed for newcomers to Mitsubishi Electric Factory Automation products gaining a background of the fundamentals and an overview of various products related to the course.


Basic to Advanced levels

These courses are designed to provide education at all levels. Various different features are explained with application examples providing an easy and informative resource for in-house company training.

Innovative next-generation, e-Manual

e-Manual Viewer

The e-Manual viewer is a next-generation digital manual offered by Mitsubishi Electric that consolidates factory automation products manuals into an easy-to-use package with various useful features integrated into the viewer. The e-Manual allows multiple manuals to be cross-searched at once, further reducing time for setting up products and troubleshooting.



Key features included

- One-stop database containing all required manuals, with local file cache
- Included with GX Works3 engineering software
- Also available in tablet version
- Easily download manuals all at once
- Multiple users can share the latest manuals and knowhow with document sharing function
- Directly port sample programs within manuals to GX Works3
- Downloaded manuals are usable offline


Windows®

iOS

Android™

e-Manual Create

e-Manual Create is software for converting word files and chm files to e-Manual documents. e-Manual Create allows users to directly refer to Mitsubishi Electric e-Manuals from user's customized device maintenance manuals and such, supporting quick troubleshooting and reduction in document creation process.



Windows®

* To obtain the Windows® version of e-Manual Viewer and e-Manual Create, please contact your local Mitsubishi Electric sales office or representative.

Product list

Model name	Outline	Station type			CC-Link IE TSN Class
		Master station	Device station		
			Local station	Remote station	
MELSEC iQ-R Series master/local module					
RJ71GN11-T2	Maximum number of connected stations: 121	●	●	-	B
MELSEC iQ-R Series CC-Link IE TSN Plus master/local module					
RJ71GN11-EIP NEW	Maximum number of connected stations: 121, EtherNet/IP™ compatible	●	●	-	B
MELSEC iQ-F Series master/local module					
FX5-CCLGN-MS	Maximum number of connected stations: 61*1	●	●	-	B
MELSEC iQ-R Series motion module					
RD78G4	Maximum number of control axes: 4	●	-	-	B
RD78G8	Maximum number of control axes: 8	●	-	-	
RD78G16	Maximum number of control axes: 16	●	-	-	
RD78G32	Maximum number of control axes: 32	●	-	-	
RD78G64	Maximum number of control axes: 64	●	-	-	
RD78GHV	High-performance type, maximum number of control axes: 128	●	-	-	
RD78GHW	High-performance type, maximum number of control axes: 256	●	-	-	
MELSEC iQ-F Series motion module					
FX5-40SSC-G	Maximum number of control axes: 4	●	-	-	B
FX5-80SSC-G	Maximum number of control axes: 8	●	-	-	
Motion control software SWM-G					
SW1DNN-SWMG-M*2	Motion control software	●	-	-	B
USB keys for motion control software					
MR-SWMG16-U	Maximum number of control axes: 16	-	-	-	-
MR-SWMG32-U	Maximum number of control axes: 32	-	-	-	-
MR-SWMG64-U	Maximum number of control axes: 64	-	-	-	-
MR-SWMG128-U	Maximum number of control axes: 128	-	-	-	-
AC servo					
MR-J5-G	MELSERVO-J5 Series servo amplifier	-	-	●	B
MR-J5W2-G	MELSERVO-J5 Series 2-axis servo amplifier	-	-	●	
MR-J5W3-G	MELSERVO-J5 Series 3-axis servo amplifier	-	-	●	
MR-J5-G-RJ	MELSERVO-J5 Series servo amplifier fully closed loop control 4-wire load-side encoder A/B/Z-phase input compatible, safety sub-function	-	-	●	
MR-J5D-G4	MELSERVO-J5 Series drive unit (1/2/3-axis)	-	-	●	
MR-JET-G	MELSERVO-JET Series servo amplifier	-	-	●	
Inverter					
FR-A800-GN	FREQROL-A800 CC-Link IE TSN supported inverter	-	-	●	B
FR-A8NCG	CC-Link IE TSN supported integrated option for FREQROL-A800 and FREQROL-F800 Series	-	-	●	
FR-E800-E	FREQROL-E800 CC-Link IE TSN supported inverter	-	-	●	A
FR-E800-SCE	FREQROL-E800 CC-Link IE TSN safety sub-function supported inverter	-	-	●	
Robot					
CR800-R	MELSEC iQ-R Series compatible robot controller FR Series*3	*4	*4	*4	B
HMI GOT2000 Series					
GT25-J71GN13-T2	CC-Link IE TSN communication unit Supported models: GT27, GT25*5	-	●	-	B

*1. For specifications of local station, please refer to the "MELSEC iQ-F FX5 User's Manual (CC-Link IE TSN) (SH(NA)-082215ENG)".

*2. For information on how to obtain the software, please contact your local Mitsubishi Electric sales office or representative.

*3. CR800-R controllers with version C2 or later, produced in or after April 2021 are supported.

*4. MELSEC iQ-R Series master/local module (RJ71GN11-T2) or CC-Link IE TSN Plus master/local module (RJ71GN11-EIP) is separately required.

*5. Not all GT25 models are supported, for more information, please refer to "GOT2000 Series catalog (L (NA) 08270ENG)".

Type	Model name	Outline	Station type			CC-Link IE TSN Class	
			Master station	Device station Local station	Remote station		
Block-type remote module							
DC input	NZ2GN2S1-16D	16 points, 24 V DC, response time 0...70 ms, positive/negative common shared spring-clamp terminal block, 1-wire	-	-	●	B/A	
	NZ2GN2S1-32D	32 points, 24 V DC, response time 0...70 ms, positive/negative common shared spring-clamp terminal block, 1-wire	-	-	●		
	NZ2GN2B1-16D	16 points, 24 V DC, response time 0...70 ms, positive/negative common shared screw terminal block, 1-wire	-	-	●		
	NZ2GN2B1-32D	32 points, 24 V DC, response time 0...70 ms, positive/negative common shared screw terminal block, 1-wire	-	-	●		
	NZ2GNCE3-32D	32 points, 24 V DC, response time 0...70 ms, positive common, sensor connector (e-CON), 3-wire	-	-	●		
	NZ2GNCF1-32D	32 points, 24 V DC, response time 0...70 ms positive/negative common, 40-pin connector, 1-wire	-	-	●		
Transistor output	NZ2GN2S1-16T	16 points, 12/24 V DC (0.5 A), sink type, spring-clamp terminal block, 1-wire	-	-	●		
	NZ2GN2S1-16TE	16 points, 12/24 V DC (0.5 A), source type, spring-clamp terminal block, 1-wire	-	-	●		
	NZ2GN2S1-32T	32 points, 12/24 V DC (0.5 A), sink type, spring-clamp terminal block, 1-wire	-	-	●		
	NZ2GN2S1-32TE	32 points, 12/24 V DC (0.5 A), source type, spring-clamp terminal block, 1-wire	-	-	●		
	NZ2GN2B1-16T	16 points, 12/24 V DC (0.5 A), sink type, screw terminal block, 1-wire	-	-	●		
	NZ2GN2B1-16TE	16 points, 12/24 V DC (0.5 A), source type, screw terminal block, 1-wire	-	-	●		
	NZ2GN2B1-32T	32 points, 12/24 V DC (0.5 A), sink type, screw terminal block, 1-wire	-	-	●		
	NZ2GN2B1-32TE	32 points, 12/24 V DC (0.5 A), source type, screw terminal block, 1-wire	-	-	●		
	NZ2GNCF1-32T	32 points, 12/24 V DC (0.1 A), sink type, 40-pin connector, 1-wire	-	-	●		
I/O combined	NZ2GN2S1-32DT	Input: 16 points, 24 V DC, response time 0...70 ms, positive common Output: 16 points, 24 V DC (0.5 A), sink type spring-clamp terminal block, 1-wire	-	-	●		
	NZ2GN2S1-32DTE	Input: 16 points, 24 V DC, response time 0...70 ms, negative common Output: 16 points, 24V DC (0.5 A), source type spring-clamp terminal block, 1-wire	-	-	●		
	NZ2GN2B1-32DT	Input: 16 points, 24 V DC, response time 0...70 ms, positive common Output: 16 points, 24 V DC (0.5 A), sink type screw terminal block, 1-wire	-	-	●		
	NZ2GN2B1-32DTE	Input: 16 points, 24 V DC, response time 0...70 ms, negative common Output: 16 points, 24 V DC (0.5 A), source type screw terminal block, 1-wire	-	-	●		
	NZ2GNCE3-32DT	Input: 16 points, 24 V DC, response time 0...70 ms, positive common Output: 16 points, 24 V DC (0.5 A), sink type sensor connector (e-CON), 3-wire	-	-	●		
Analog input	NZ2GN2S-60AD4	4 channels, input: -10...10 V DC, 0...20 mA DC conversion speed: 200 μs/channel, spring-clamp terminal block	-	-	●		
	NZ2GN2B-60AD4	4 channels, input: -10...10 V DC, 0...20 mA DC conversion speed: 200 μs/channel, screw terminal block	-	-	●		
Analog output	NZ2GN2S-60DA4	4 channels, output: -10...10 V DC, 0...20 mA DC conversion speed: 200 μs/channel, spring-clamp terminal block	-	-	●		
	NZ2GN2B-60DA4	4 channels, output: -10...10 V DC, 0...20 mA DC conversion speed: 200 μs/channel, screw terminal block	-	-	●		
Waterproof/dustproof type (IP67) remote module							
DC input	NZ2GN12A4-16D	16 points, 24 V DC, response time 0...70 ms, positive common waterproof connector, 2- to 4-wire	-	-	●	B/A	
	NZ2GN12A4-16DE	16 points, 24 V DC, response time 0...70 ms, negative common waterproof connector, 2- to 4-wire	-	-	●		
Transistor output	NZ2GN12A2-16T	16 points, 12/24 V DC (2A, 4A), sink type, waterproof connector, 2-wire	-	-	●		
	NZ2GN12A2-16TE	16 points, 12/24 V DC (2A, 4A), source type, waterproof connector, 2-wire	-	-	●		
I/O combined	NZ2GN12A42-16DT	Input: 8 points, 24 V DC, response time 0...70 ms, positive common, 2- to 4-wire Output: 8 points, 12/24 V DC (2A, 4A), sink type, 2-wire, waterproof connector	-	-	●		
	NZ2GN12A42-16DTE	Input: 8 points, 24 V DC, response time 0...70 ms, negative common, 2- to 4-wire Output: 8 points, 12/24 V DC (2A, 4A), source type, 2-wire, waterproof connector	-	-	●		
Block-type remote module with safety functions							
DC input	NZ2GNSS2-8D	Single wiring: 8 points/double wiring: 4 points, 24 V DC response time 1...70 ms, negative common spring-clamp terminal block, 2-wire	-	-	●	B	
Transistor output	NZ2GNSS2-8TE	Single wiring: 8 points/double wiring: 4 points, 24 V DC (0.5 A) source + source type, spring-clamp terminal block, 2-wire	-	-	●		
I/O combined	NZ2GNSS2-16DTE	Input: 8 points (single wire)/4 points (double wire), 24 V DC response time 1...70 ms, negative common Output: 8 points (single wire)/4 points (double wire), 24 V DC (0.5 A) source + source type, spring-clamp terminal block, 2-wire	-	-	●		
Managed Ethernet switch							
NZ2MHG-TSNT8F2			10 Mbps/100 Mbps/1 Gbps, Auto MDI/MDI-X, DIN rail, 8 ports	-	-	-	B
Bridge module							
NZ2AW1GNAL			CC-Link IE TSN-AnyWireASLINK bridge module	-	-	●	B

Partner products

Model name	Outline	CC-Link IE TSN Class
Industrial switching hub		
DT135TXA	10 Mbps/100 Mbps/1 Gbps Auto MDI/MDI-X, DIN rail, 5 ports, manufactured by Mitsubishi Electric System & Service Co., Ltd.	A
Ethernet cable		
SC-E5EW-S□M NEW	Double shielded cable, Category 5e, for indoor use, manufactured by Mitsubishi Electric System & Service Co., Ltd.	-
SC-E5EW-S□M-MV NEW	Double shielded cable, Category 5e, for indoor movable part, manufactured by Mitsubishi Electric System & Service Co., Ltd.	-
SC-E5EW-S□M-L NEW	Double shielded cable, Category 5e, for indoor/outdoor use, manufactured by Mitsubishi Electric System & Service Co., Ltd.	-
Inline coupler		
SPAD-RJ45S-E5E NEW	RJ-45 connector with shield, manufactured by Mitsubishi Electric System & Service Co., Ltd.	-

Development kit/tool

Type	Model	Outline	CC-Link IE TSN Class
Master station communication LSI	NZ2GACP610-60	Dedicated communication LSI (CP610) 60 pieces	*2
Master station software development kit	SW1DTD-GNSDK1M-M*1	Library with source code provided, "INtime" version	
	SW1DTD-GNSDK2M-M*1	Library provided, "INtime" version	
Remote station communication LSI	NZ2GACP620-60	Communication LSI embedded with GbE-PHY (CP620) 60 pieces	*2
	NZ2GACP620-300	Communication LSI embedded with GbE-PHY (CP620) 300 pieces	
CC-Link IE TSN communication software for Windows®	SW1DND-CCIETCT-M	Computer-based CC-Link IE TSN data collection software	-

*1. Contract is necessary to purchase a software development kit (SDK). For further details, please contact your local Mitsubishi Electric office or representative.

*2. Can be used for development of class B.

Android and Google Play are trademarks of Google LLC.
App Store is a service mark of Apple Inc.
CANopen is a registered trademark of CAN in Automation e.V.
Edgex is a registered trademark of the Edgex Consortium.
EtherNet/IP is a trademark of ODVA, Inc.
IOS is a registered trademark of Cisco in the U.S. and other countries and is used under license.
Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States and other countries.
OPC UA logo is a registered trademark of OPC Foundation.
PCI Express is a registered trademark of PCI-SIG.
The name PLCopen® is a registered trademark owned by the association PLCopen.
QR Code is a trademark or a registered trademark of DENSO WAVE INCORPORATED in JAPAN, the United States and/or other countries.
All other company names and product names used in this document are trademarks or registered trademarks of their respective companies.


Precautions before use

This publication explains the typical features and functions of the products herein and does not provide restrictions or other information related to usage and module combinations. Before using the products, always read the product user manuals. Mitsubishi Electric will not be held liable for damage caused by factors found not to be the cause of Mitsubishi Electric; opportunity loss or lost profits caused by faults in Mitsubishi Electric products; damage, secondary damage, or accident compensation, whether foreseeable or not, caused by special factors; damage to products other than Mitsubishi Electric products; or any other duties.

For safe use

- To use the products given in this publication properly, always read the relevant manuals before beginning operation.
- The products have been manufactured as general-purpose parts for general industries, and are not designed or manufactured to be incorporated in a device or system used in purposes related to human life.
- Before using the products for special purposes such as nuclear power, electric power, aerospace, medicine or passenger-carrying vehicles, consult with Mitsubishi Electric.
- The products have been manufactured under strict quality control. However, when installing the products where major accidents or losses could occur if the products fail, install appropriate backup or fail-safe functions in the system.

YOUR SOLUTION PARTNER



Mitsubishi Electric offers a wide range of automation equipment from PLCs and HMIs to CNC and EDM machines.

A NAME TO TRUST

Since its beginnings in 1870, some 45 companies use the Mitsubishi name, covering a spectrum of finance, commerce and industry.

The Mitsubishi brand name is recognized around the world as a symbol of premium quality.

Mitsubishi Electric Corporation, established in 1921, is active in space development, transportation, semi-conductors, energy systems, communications and information processing, audio visual equipment and home electronics, building and energy management and automation systems, and has 183 factories, laboratories and offices worldwide in over 140 countries.

This is why you can rely on Mitsubishi Electric automation solution - because we know first hand about the need for reliable, efficient, easy-to-use automation and control in our own factories.

As one of the world's leading companies with a global turnover of over 4 trillion Yen (over \$40 billion), employing over 146,000 people, Mitsubishi Electric has the resource and the commitment to deliver the ultimate in service and support as well as the best products.



Low-voltage Power Distribution Products



Transformers, Med-voltage Distribution Products



Power Monitoring and Energy Saving Products



Power (UPS) and Environmental Products



Compact and Modular Controllers



Servos, Motors and Inverters



Visualization: HMIs



Edge Computing Products



Numerical Control (NC)



Collaborative and Industrial Robots



Processing machines: EDM, Lasers

* Not all products are available in all countries.

Country/Region	Sales office	Tel/Fax
USA	MITSUBISHI ELECTRIC AUTOMATION, INC. 500 Corporate Woods Parkway, Vernon Hills, IL 60061, U.S.A.	Tel : +1-847-478-2100 Fax : +1-847-478-2253
Mexico	MITSUBISHI ELECTRIC AUTOMATION, INC. Mexico Branch Boulevard Miguel de Cervantes Saavedra 301, Torre Norte Piso 5, Ampliacion Granada, Miguel Hidalgo, Ciudad de Mexico, Mexico, C.P.115200	Tel : +52-55-3067-7512
Brazil	MITSUBISHI ELECTRIC DO BRASIL COMERCIO E SERVICOS LTDA. Avenida Adelino Cardana, 293, 21 andar, Bethaville, Barueri SP, Brasil	Tel : +55-11-4689-3000 Fax : +55-11-4689-3016
Germany	MITSUBISHI ELECTRIC EUROPE B.V. German Branch Mitsubishi-Electric-Platz 1, 40882 Ratingen, Germany	Tel : +49-2102-486-0 Fax : +49-2102-486-7780
UK	MITSUBISHI ELECTRIC EUROPE B.V. UK Branch Travellers Lane, UK-Hatfield, Hertfordshire, AL10 8XB, U.K.	Tel : +44-1707-28-8780 Fax : +44-1707-27-8695
Ireland	MITSUBISHI ELECTRIC EUROPE B.V. Irish Branch Westgate Business Park, Ballymount, Dublin 24, Ireland	Tel : +353-1-4198800 Fax : +353-1-4198890
Italy	MITSUBISHI ELECTRIC EUROPE B.V. Italian Branch Centro Direzionale Colleoni - Palazzo Sirio, Viale Colleoni 7, 20864 Agrate Brianza (MB), Italy	Tel : +39-039-60531 Fax : +39-039-6053-312
Spain	MITSUBISHI ELECTRIC EUROPE, B.V. Spanish Branch Carretera de Rubi, 76-80-Apdo. 420, E-08190 Sant Cugat del Valles (Barcelona), Spain	Tel : +34-935-65-3131 Fax : +34-935-89-1579
France	MITSUBISHI ELECTRIC EUROPE B.V. French Branch 25, Boulevard des Bouvets, 92741 Nanterre Cedex, France	Tel : +33-1-55-68-55-68 Fax : +33-1-55-68-57-57
Czech Republic	MITSUBISHI ELECTRIC EUROPE B.V. Czech Branch, Prague Office Pekarska 621/7, 155 00 Praha 5, Czech Republic	Tel : +420-255-719-200
Poland	MITSUBISHI ELECTRIC EUROPE B.V. Polish Branch ul. Krakowska 48, 32-083 Balice, Poland	Tel : +48-12-347-65-00
Sweden	MITSUBISHI ELECTRIC EUROPE B.V. (Scandinavia) Hedvig Mollersgata 6, 223 55 Lund, Sweden	Tel : +46-8-625-10-00 Fax : +46-46-39-70-18
Russia	MITSUBISHI ELECTRIC (RUSSIA) LLC St. Petersburg Branch Piskarevsky pr. 2, bld 2, lit "Sch", BC "Benua", office 720; 195027 St. Petersburg, Russia	Tel : +7-812-633-3497 Fax : +7-812-633-3499
Turkey	MITSUBISHI ELECTRIC TURKEY A.S. Umraniye Branch Serifali Mah. Kale Sok. No:41 34775 Umraniye - Istanbul, Turkey	Tel : +90-216-969-2500 Fax : +90-216-661-4447
UAE	MITSUBISHI ELECTRIC EUROPE B.V. Dubai Branch Dubai Silicon Oasis, P.O.BOX 341241, Dubai, U.A.E.	Tel : +971-4-3724716 Fax : +971-4-3724721
South Africa	ADROIT TECHNOLOGIES 20 Waterford Office Park, 189 Witkoppen Road, Fourways, South Africa	Tel : +27-11-658-8100 Fax : +27-11-658-8101
China	MITSUBISHI ELECTRIC AUTOMATION (CHINA) LTD. Mitsubishi Electric Automation Center, No.1386 Hongqiao Road, Shanghai, China	Tel : +86-21-2322-3030 Fax : +86-21-2322-3000
Taiwan	SETSUYO ENTERPRISE CO., LTD. 6F, No.105, Wugong 3rd Road, Wugu District, New Taipei City 24889, Taiwan	Tel : +886-2-2299-2499 Fax : +886-2-2299-2509
Korea	MITSUBISHI ELECTRIC AUTOMATION KOREA CO., LTD. 7F to 9F, Gangseo Hangang Xi-tower A, 401, Yangcheon-ro, Gangseo-Gu, Seoul 07528, Korea	Tel : +82-2-3660-9569 Fax : +82-2-3664-8372
Singapore	MITSUBISHI ELECTRIC ASIA PTE. LTD. 307 Alexandra Road, Mitsubishi Electric Building, Singapore 159943	Tel : +65-6473-2308 Fax : +65-6476-7439
Thailand	MITSUBISHI ELECTRIC FACTORY AUTOMATION (THAILAND) CO., LTD. 12th Floor, SV.City Building, Office Tower 1, No. 896/19 and 20 Rama 3 Road, Kwaeng Bangpongpan, Khet Yannawa, Bangkok 10120, Thailand	Tel : +66-2682-6522-31 Fax : +66-2682-6020
Vietnam	MITSUBISHI ELECTRIC VIETNAM COMPANY LIMITED Unit 01-04, 10th Floor, Vincom Center, 72 Le Thanh Ton Street, District 1, Ho Chi Minh City, Vietnam	Tel : +84-28-3910-5945 Fax : +84-28-3910-5947
Indonesia	PT. MITSUBISHI ELECTRIC INDONESIA Gedung Jaya 8th Floor, JL. MH. Thamrin No.12, Jakarta Pusat 10340, Indonesia	Tel : +62-21-31926461 Fax : +62-21-31923942
India	MITSUBISHI ELECTRIC INDIA PVT. LTD. Pune Branch Emerald House, EL-3, J Block, M.I.D.C., Bhosari, Pune-411026, Maharashtra, India	Tel : +91-20-2710-2000 Fax : +91-20-2710-2100
Australia	MITSUBISHI ELECTRIC AUSTRALIA PTY. LTD. 348 Victoria Road, P.O. Box 11, Rydalmere, N.S.W 2116, Australia	Tel : +61-2-9684-7777 Fax : +61-2-9684-7245

MITSUBISHI ELECTRIC CORPORATION
HEAD OFFICE: TOKYO BLDG., 2-7-3, MARUNOUCHI, CHIYODA-KU, TOKYO 100-8310, JAPAN
www.MitsubishiElectric.com